



**ARAMIDE TENSILE CORD FOR HIGH  
STRENGTH AND VERY LOW STRETCH.**

**NEOPRENE RUBBER FOR HIGH GRIP,  
FLEXABILITY, AND LONG BELT LIFE.**

WT: 0.5lbs [0.23 kgs]

THIS DOCUMENT IS THE PROPERTY  
OF PAXTON PRODUCTS AND IS  
FURNISHED ON THE CONDITION  
THAT IT IS TO BE USED ONLY BY  
PAXTON CUSTOMERS FOR  
INTEGRATING PAXTON  
EQUIPMENT. THIS DOCUMENT  
MAY BE USED BY CUSTOMERS TO  
CREATE THEIR OWN EQUIPMENT  
DOCUMENTATION. OTHERWISE  
THIS DOCUMENT IS NOT TO BE  
USED IN ANY SHAPE OR FORM TO  
CREATE DOCUMENTS, PARTS, OR  
EQUIPMENT.

**PAXTON**  
PRODUCTS

10125 Carver Road  
Cincinnati, OH 45242

Phone: (800) 441-7475  
(513) 891-7474

[www.paxtonproducts.com](http://www.paxtonproducts.com)

**BELT, 16GRV, POLY-RIB, 380 LG**  
**PAXTON COMPOSITE CONSTRUCTION**

DATE

3/31/2010

INVENTOR DWG No.

**CS-8001035**