

### Paxton Two Stage Replacement Silencer Cartridge

MODEL # 1200-Silencer



<b>Item Number</b>	1200-Silencer	
<b>Description</b>	Replacement Silencer Cartridge	
<b>Fits blowers</b>	PX-300, PX-500, PX-750, AT-700, AT-800, AT-1200, XT-500	
<b>Weight</b>	2 lbs	0.9 kg
<b>Dimensions</b>		
<b>Length</b>	6 3/4 in	171 mm
<b>Diameter</b>	5 1/2 in	140 mm

### Recommended Replacement Frequency

Paxton part	1 or 2 shifts/day operation	3 shifts/day operation
<b>Belts</b>	12 months	6 months or 4000 hours
<b>Belt Springs</b>	12 months	6 months or 4000 hours
<b>Tensioners</b>	24 months	12 months
<b>Filters</b>	Filters must be changed as often as needed to maintain blower or system performance as measured by increased pressure drop across the filter. The filter must be changed if the pressure drop exceeds 10" of water column. Filter change frequency will vary widely based on environmental and atmospheric conditions. Minimum recommended filter change frequency is every 12 months for 1 or 2 shift/day operation; and every 6 months for 3 shift/day operation.	
<b>Silencer</b>	Inspect when replacing filters. Change annually in typical applications. In harsh or high humidity environments, change every 2000 hours.	

